GRUNDFOS CMB PM1 BOOSTER

Grundfos CMB PM1 Booster is ideal for instant water heater showers while providing strong, constant water pressure around your house and garden. The CMB PM1 Booster is a compact, quiet yet powerful multistage pump with built-in pressure control and maintenance free design.





Product certified by SIRIM



Quiet operation



2 years warranty



Dry running protection



Quality assurance



Longer life span



Spacesaving




Easy installation






PHYSICAL ATTRIBUTES

C & E



PERFORMANCE CURVE



Model	Motor Power P2 (kW)	Connections		Dimensions (mm)				Weight	
		Inlet	Outlet	A (I)	B (w)	C (h)	D (inlet)	E (outlet)	(kg)
CMB 3-37 PM1	0.50	1" Female	1" Male	324	158	315	75	315	14
CMB 3-46 PM1	0.50	1" Female	1" Male	342	158	315	75	315	14
CMB 5-37 PM1	0.67	1¼" Female	1" Male	364	158	315	75	315	15
CMB 5-46 PM1	0.90	1¼" Female	1" Male	382	158	315	75	315	15

OPERATING CONDITIONS

Ambient Temperature	0°C to +55°C
Liquid Temperature	0°C to +60°C
System Pressure	Max. 10 bar

TECHNICAL DATA

Power Supply Voltage	CMB 3 Range> 220-230 Volt, 50 Hz CMB 5 Range> 220-240 Volt, 50 Hz
Power Supply Cable	2 m with plug
Enclosure Class	Undercover installation recommended (IP55)
Approvals and Markings	Listed & Registred in SPAN SIRIM Certified

POSITIVE INLET PRESSURE (WATER ABOVE PUMP LEVEL)





SELECTION GUIDE - MAKE THE RIGHT CHOICE

CMB PM1 MODELS	Solar/Electric Sto	Instant Electric Hot Water		
CMB FMI MODELS	Normal Shower	Rain Shower	Heater	
CMB 3-37 PM1	1-3 Bathrooms	1 Bathroom	1-3 Bathrooms	
CMB 3-46 PM1	1-3 Bathrooms	1-2 Bathrooms	1-3 Bathrooms	
CMB 5-37 PM1	4-5 Bathrooms	3-4 Bathrooms	4-5 Bathrooms	
CMB 5-46 PM1	6 Bathrooms	5 Bathrooms	6 Bathrooms	

GRUNDFOS PUMPS SDN BHD (202527-A)

7, Jalan Peguam U1/25, Glenmarie Industrial Park, 40150 Shah Alam, Selangor Tel: +603-5032 1900 | Fax: +603-5032 1732 Toll Free: 1800 88 PUMP (7867)



